



NEW

Carrytank® 150

Polyethylene tank for gasoline transport



Description

The CARRYTANK® 150 for gasoline, is a transportable tank for gasoline produced in linear polyethylene with rotational molding, designed and conceived to be as compact as possible and to have the best external dimensions/useful capacity ratio existing on the market; this allows it to be used in pick-ups with or without a bed cover, the transport with all the most common vehicles and facilitates the shipment. Version for diesel is available. AdBlue®/DEF version is also available.

Main features

Emiliana Serbatoi's gasoline transport tanks offer the ideal solution for transporting gasoline safely and in compliance with all applicable regulations. Our transportable gasoline tanks are manufactured from a specific material that provides complete safety guarantees and resistance to the corrosive effects of gasoline. All components of our gasoline tanks are also ATEX certified.

The tank, despite its compact size, is equipped with:

- padlockable lid and reinforced closure
- aluminum filling plug
- safety valve
- transfer unit
- forklift pockets for lifting handles for lifting when empty
- recesses for securing straps to the support base
- level gauge
- inserts in aluminum or material compatible with gasoline fuel.

Outfittings

Tank made in a specific material able to confer safety warranty and chemical resistance to the aggression of all types of petrols. It is provided with:

Configuration model EE:

- 12V Pump ATEX Certified, flowrate 30 lit/min.
- 4 mt antistatic hose.
- ATEX automatic nozzle.
- 5 mt electrical cable with bipolar connector.
- 4 mt grounding cable with crocodile clamps.

Accessories petrol



ES Filter

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 10µm. Flow rate 70 l/min.



Filter Water captor 70

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 30µm. Flow rate 70 l/min.



Digital flow meter for gasoline K24 ATEX



Drip Tray

Technical data

Model	Nominal capacity (lt)	Width (mm)	Depth (mm)	Highness (mm)	Thickness (mm)	Empty weight (kg)	Weight with pump unit (kg)
CTK150	150	985	585	465	9	23	38

Loading Plan

Model	Container 20'	Container 40'	Container 40' HC	Std truck 2700h mm
CTK150	80	168	210	260

Product code

CT	X	X	X	X
Model	Fuel	Volume	Pump	Nozzle
CT = Carrytank	K = Diesel and gasoline homologated	150 = 150 l	J = 30 l/min Atex	E = Automatic Atex 60 l/min

Approval



Transportable materials	Diesel / UNI1202 Gasoline / UNI1203
Clases ADR	3
Packaging group	II - III