



Carrytank® 330

Polyethylene tank for Diesel and gasoline fuel transport equipped with a fuel transfer unit



Description

Carrytank® 330 and 440 are tanks made in linear polyethylene designed for Diesel fuel transport; it is equipped with the following fittings: lockable lid, filling plug, with integrated air vent device, level indicator, in-line filter, fuel transfer unit, automatic fuel nozzle, built-in forklift pockets (full tank), handles for lifting and carrying (empty tank) and integrated recesses for securing with ratchet lashing straps during transport. All the fittings are made of aluminum or materials compatible with Diesel fuel. Gasoline transport version is also available.

AdBlue®/DEF transport version is also available.

Pick-up line version is also available.

Outfittings

Standard configuration model AC:

- DC fuel transfer pump, mod. DEVIL40 (12 or 24 V), flow rate 40 l/min.
- 4 m of hose.
- Automatic nozzle.
- 6 m of battery power cable and clamps for battery connection.
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter


Configuration model DF:

- DC fuel transfer pump, mod. DPUMP (12 or 24 V), flow rate 60 l/min.
- 4 m of hose.
- Automatic nozzle.
- 6 m of battery power cable and clamps for battery connection.
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

Configuration model BC:

- AC fuel transfer pump, mod. DEVIL55 (230 V), flow rate 55 l/min.
- 4 m of hose.
- Automatic nozzle.
- 2 m of power cable with Schuko plug for connection to 230v supply (Diesel fuel).
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

Accessories



Digital fuel meter, mod. M24, for Diesel Fuel



Strainer filter stainless steel

For diesel and gasoline. Impurity filtration. Filter capacity 60µm. Flow rate 50 l/min.



ES Filter

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 10µm. Flow rate 70 l/min.



Filter Water captor 70

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 30µm. Flow rate 70 l/min.



Manganese 12V battery with battery charger (European plug type C) and battery slot



Manganese 12V battery with battery charger (cigarette lighter plug) and battery slot



Drip Tray



Retention Basin for Carrytank

Retention basin for ground use, 100% tank's volume capacity, made in carbon steel.

Technical data

Model	Nominal capacity (lt)	Width (mm)	Depth (mm)	Highness (mm)	Thickness (mm)	Empty weight (kg)	Weight with pump unit (kg)
CT330	330	1,200	800	650	6,5	32	44

Loading Plan

Model	Container 20'	Container 40'	Container 40' HC	Std truck 2700h mm
CT330	30	66	88	100

Product code

CT	X	X	X	X
Model CT = Carrytank	Fuel G = Diesel	Volume 330 = 330 l	Pump A = 40 l/min B = 55 l/min D = 60 l/min	Nozzle C = Automatic 60 l/min F = Automatic 80 l/min
Gasoline not available for the Italian market - Not all combinations are available				