





Carrytank® CTK 900 Gasoline

Polyethylene tank for gasoline transport



Description

Carrytank® 900 for gasoline is a polyethylene tank for the transport of gasoline fuel (900 litres) with lockable lid. Diesel version is also available.

The new tank with patent pending has successfully passed the toughest stress tests in order to obtain the ADR/RID/ADN and IMDG approval for fuel transport:

- Drop test
- Vibration test
- Hydraulic pressure test
- Pneumatic pressure test
- Full load lifting test
- Stackability test at full load

Since it is a tank intended for the transport, the design research has also focused on logistics, with the aim of making its handling faster and more efficient. For this reason, the tank, in addition to the forklift pockets, is also equipped with 4 lifting lugs for lifting tank at full load from above, ensuring full stackability during the storage.

Main features

Emiliana Serbato's gasoline portable tanks are the ideal solution for safely transporting gasoline in full compliance with all current regulations. Our portable gasoline tanks are made of a specific material that provides complete safety guarantees and resistance to gasoline corrosion. Furthermore, all components of our gasoline tanks are ATEX certified.

Made in linear polyethylene, it is equipped with:

- reinforced lockable lid
- filling aluminium plug with integrated air vent device
- fuel transfer unit
- built-in forklift pockets for lifting fully loaded from below
- lifting lugs for lifting fully loaded from above and for fixing fastening straps
- new plug-in quick connections
- all the fittings are made of aluminium or materials compatible with gasoline fuel.

Outfittings

GASOLINE OUTFITTINGS

Configuration model EE:

- 12V Pump mod. EX50 12V ATEX Certified, flowrate 45 lit/min.
- 4 mt antistatic hose.
- ATEX automatic nozzle.
- 5 mt electrical cable with bipolar connector.
- 4 mt grounding cable with crocodile clamps.

Accessories petrol



Drip Tray



Filter Water captor 70

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 30µm. Flow rate 70 l/min.



Digital flow meter for gasoline K24 ATEX



ES Filter

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 10µm. Flow rate 70 l/min.

Technical data

Model	Nominal capacity (lt)	Width (mm)	Depth (mm)	Highness (mm)	Weight with pump unit (kg)
CTK900	900	1,530	1,150	910	105

Loading Plan

Model	Container 20'	Container 40'	Container 40' HC	Std truck 2700h mm
CTK900	14	30	30	34

Product code

CT	X	X	X	X
Model	Fuel	Volume	Pump	Nozzle
CT = Carrytank	K = Gasoline homologated	900 = 900 l	E = Atex 50 l/min	E = Automatic Atex 60 l/min

Approval



Transportable materials	Diesel / UNI1202 Gasoline / UNI1203
Clases ADR	3
Packaging group	II - III