




# Carrytank® CTK 330 Gasoline

Polyethylene tank for gasoline transport



## Description

Carrytank CTK 330 is the new 330-liter polyethylene tank with padlockable lid for transporting gasoline. The CTK 330 is based on the long track record of ES in the development of tanks in the digital environment; the tank, made entirely of polyethylene, is capable of storing and transporting up to 330 liters of diesel fuel or gasoline in complete safety, complying with the tests required by ADR (road transport), IMDG (sea transport), AND (transport on inland waters) and RID (rail transport). The innovative aspect of the CARRYTANK® 330 is its design developed entirely in a digital environment, using a technology that originated with the CARRYTANK 900+100 and was fully developed within ES. Also available in diesel version.

## Main features

Emiliana Serbato's gasoline transport tanks offer the ideal solution for transporting gasoline safely and in compliance with all applicable regulations. Our transportable gasoline tanks are manufactured from a specific material that provides complete safety guarantees and resistance to the corrosive effects of gasoline. All components of our gasoline tanks are also ATEX certified.

It is compatible with the most common filtration systems and comes with:

- aluminum filling plug
- safety valve
- level gauge
- transfer unit
- forklift pockets for lifting
- handles for lifting when empty
- recesses for securing straps to the support base

## Outfittings

### GASOLINE OUTFITTINGS

Configuration model EE:

- 12V Pump mod. EX50 12V ATEX Certified, flowrate 45 lit/min.
- 4 mt antistatic hose.
- ATEX automatic nozzle.
- 5 mt electrical cable with bipolar connector.
- 4 mt grounding cable with crocodile clamps.
- Optional: ATEX digital flow meter.
- Optional: water separator filter.

## Accessories petrol



ES Filter

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 10µm. Flow rate 70 l/min.



Filter Water captor 70

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 30µm. Flow rate 70 l/min.



Digital flow meter for gasoline K24 ATEX



Drip Tray

## Technical data

| Model  | Nominal capacity (lt) | Width (mm) | Depth (mm) | Thickness (mm) | Highness (mm) | Empty weight (kg) | Weight with pump unit (kg) |
|--------|-----------------------|------------|------------|----------------|---------------|-------------------|----------------------------|
| CTK330 | 330                   | 1,295      | 885        | 11             | 655           | 53                | 65                         |

## Loading Plan

| Model  | Container 20' | Container 40' | Container 40' HC | Std truck 2700h mm |
|--------|---------------|---------------|------------------|--------------------|
| CTK330 | 30            | 66            | 88               | 100                |

## Product code

| CT             | X                        | X           | X                 | X                           |
|----------------|--------------------------|-------------|-------------------|-----------------------------|
| Model          | Fuel                     | Volume      | Pump              | Nozzle                      |
| CT = Carrytank | K = Gasoline homologated | 330 = 330 l | E = Atex 50 l/min | E = Automatic Atex 60 l/min |

Not all combinations are available

Approval



|                         |                                           |
|-------------------------|-------------------------------------------|
| Transportable materials | Diesel / UNI1202<br>Gasoline /<br>UNI1203 |
| Clases ADR              | 3                                         |
| Packaging group         | II - III                                  |